

LORO-X ANSCHLUßSTÜCK KA-MU 250/LX-ML 150

LORO-X connecting piece KA socket 250/LX-ML 150 eccentric form 2

Popis

LORO-X connector made of steel, hot-dip galvanized, from LORO-X pipe DN150 to plastic pipe socket DN250, eccentric, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, DN150/250




Údaje o artikli

EAN kód	4038088085745
ETIM trieda	EC003024
Menovitý priemer	DN 150
Vonkajšie rozmery (VxŠxH)	273 x 273 x 284 mm
Hmotnosť	6,50 Kg (STK)
Skupina produktov	1
Colný sadzobník	73089098
Materiál / Farba	Stahl feuerverzinkt, Silber

Pokyny na použitie

kein Verwendungshinweis notwendig



Na stiahnutie



Alles online

[Návod na montáž \(PDF\)](#)

[Certifikát \(PDF\)](#)

[BIM 3D \(STEP\)](#)

[Rozmerový výkres \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)

[Prospekt \(PDF\)](#)

[CAD 3D \(DWG\)](#)