

LORO-X ANSCHLUßST.VON MUFFENL.AN KA-MUFF

LORO-X connection piece from socketless to KA socket DN 250

Popis

LORO-XML connector, made of steel, hot-dip galvanized, without socket, in accordance with DIN EN 1123 with raised quality standard, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, approval no. Z-42.1-346 from DIBt, DN250/250




Údaje o artiklu

EAN kód	4038088068281
ETIM třída	EC003024
Jmenovitý průměr	DN 250, DN 250
Vnější rozměry (VxŠxD)	273 x 273 x 260 mm
Hmotnost	6,90 Kg (STK)
Skupina produktů	1
Celní sazebník	73089098
Materiál / Barva	Stahl feuerverzinkt, Silber

Pokyny k použití

LORO-XML Stahlabflussrohre muffenlos in DN 250 und DN 300, aus Stahl, feuerverzinkt. Für große Nennweiten hat LORO muffenlose Stahlabflusssysteme für die Regenentwässerung in DN 250 und DN 300 mit bauaufsichtlicher Zulassung Nr. Z-42.1-346 vom DIBt in sein Entwässerungsprogramm aufgenommen. Durch die Verwendung einer muffenlosen Verbindung wird die Verlegung mit einem CV-Verbinder für große Nennweiten wesentlich vereinfacht.



Ke stažení



Alles online

[Návod k instalaci \(PDF\)](#)

[Certifikát \(PDF\)](#)

[Výkres rozměrů \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Prospekt \(PDF\)](#)

[CAD \(DWG\)](#)