

LORO-X ANSCHLUßST.VON MUFFENL.AN KA-MUFF

LORO-X connection piece from socketless to KA socket DN 300

Opis

LORO-XML connector, made of steel, hot-dip galvanized, without socket, in accordance with DIN EN 1123 with raised quality standard, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, approval no. Z-42.1-346 from DIBt, DN300/300




Podaci o artiklu

EAN kod	4038088068298
ETIM klasa	EC003024
Nazivni promjer	DN 300, DN 300
Vanjske mjere (VxŠxD)	324 x 324 x 290 mm
Težina	9,40 Kg (STK)
Grupa proizvoda	1
Carinski tarifni broj	73089098
Materijal / Boja	Stahl feuerverzinkt, Silber

Napomena za upotrebu

LORO-XML Stahlabflussrohre muffenlos in DN 250 und DN 300, aus Stahl, feuerverzinkt. Für große Nennweiten hat LORO muffenlose Stahlabflusssysteme für die Regenentwässerung in DN 250 und DN 300 mit bauaufsichtlicher Zulassung Nr. Z-42.1-346 vom DIBt in sein Entwässerungsprogramm aufgenommen. Durch die Verwendung einer muffenlosen Verbindung wird die Verlegung mit einem CV-Verbinder für große Nennweiten wesentlich vereinfacht.



Preuzimanja



Alles online

[Upute za ugradnju \(PDF\)](#)

[Certifikat \(PDF\)](#)

[Dimenzijski crtež \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Prospekt \(PDF\)](#)

[CAD \(DWG\)](#)