

LX-EINSCHIEBMUFFE DN100 T3=220

LORO-X insertion sleeve T3 = 220 mm, DN 100

Description

LORO-X slip-in socket made of steel, hot-dip galvanized, T3 = 220 mm, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, DN100




Données de l'article

Code EAN	4038088103395
Classe ETIM	EC003024
Diamètre nominal	DN 100
Dimensions extérieures (HxLxP)	118 x 118 x 310 mm
Poids	1,60 Kg (STK)
Groupe de produits	1
Numéro tarifaire douanier	73089098
Matériau / Couleur	Stahl feuerverzinkt, Silber

Note d'utilisation

kein Verwendungshinweis notwendig



Téléchargements



Alles online

[Notice d'installation \(PDF\)](#)

[Certificat \(PDF\)](#)

[BIM 3D \(STEP\)](#)

[Dessin dimensionnel \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)

[Brochure \(PDF\)](#)

[CAD 3D \(DWG\)](#)