


LORO-X PIPE WITH 1 SOCKET 3000 MM DN 125

LORO-X pipe 1 socket 3000 mm DN 125

Beskrivelse

LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 3000 mm, + 1socket, DN125



Artikkeldata

EAN-kode	4038088004784
ETIM-klasse	EC011386
Nominell diameter	DN 125
Nominell lengde/grad	3000
Utvendige mål (HxBxL)	152 x 152 x 3075 mm
Vekt	27,40 Kg (STK)
Produktgruppe	1
Tolltariffnummer	73063018
Materiale / Farge	Stahl feuerverzinkt, Silber

Bruksanvisning

Die Nenn-Länge (l) der Rohre wird ohne Länge der Muffe angegeben und kann daher zum Auszählen der Rohre in zusammengestecktem Zustand herangezogen werden. Beispiel: Nenn-Länge 1000 mm + 70 mm Muffe = 1070 mm Rohr-Außenmaß.

Nedlastinger



Alles online

[Monteringsanvisning \(PDF\)](#)
[Godkjenning \(PDF\)](#)
[BIM 3D \(STEP\)](#)
[BIM Revit \(RFA\)](#)
[Måltegning \(PDF\)](#)
[CAD 2D \(DXF\)](#)
[BIM IFC4 \(parametrisk\)](#)
[Brosjyre \(PDF\)](#)
[CAD 3D \(DWG\)](#)
[BIM 3D \(IFC\)](#)