

LORO-X PIPE WITH 1 SOCKET 5000 MM DN 125

LORO-X pipe 1 socket 5000 mm DN 125

Opis

LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 5000 mm, + 1socket, DN125




Dane artykułu

Kod EAN	4038088005262
Klasa ETIM	EC011386
Średnica nominalna	DN 125
Długość/stożek nominalny	5000
Wymiary zewnętrzne (WxSxD)	152 x 152 x 5075 mm
Waga	43,00 Kg (STK)
Grupa produktów	1
Numer taryfy celnej	73063018
Materiał / Kolor	Stahl feuerverzinkt, Silber

Wskazówki dotyczące użytkowania

Die Nenn-Länge (l) der Rohre wird ohne Länge der Muffe angegeben und kann daher zum Auszählen der Rohre in zusammengestecktem Zustand herangezogen werden. Beispiel: Nenn-Länge 1000 mm + 70 mm Muffe = 1070 mm Rohr-Außenmaß.



Pobieranie



Alles online

[Instrukcja montażu \(PDF\)](#)

[Certyfikat \(PDF\)](#)

[BIM IFC4 \(parametryczny\)](#)

[Rysunek wymiarowy \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Broszura \(PDF\)](#)

[CAD \(DWG\)](#)