


LORO-X PIPE WITHOUT SOCKET 3000 MM DN 300

LORO-X pipe socketless 3000 mm DN 300

Description

LORO-XML pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, approval no. Z-42.1-346 from DIBt, 3000 mm, without socket, DN300



Données de l'article

Code EAN	4038088068052
Classe ETIM	EC011386
Diamètre nominal	DN 300
Longueur/degré nominal	3000
Dimensions extérieures (HxLxP)	324 x 324 x 3000 mm
Poids	96,00 Kg (STK)
Groupe de produits	1
Numéro tarifaire douanier	73063018
Matériau / Couleur	Stahl feuerverzinkt, Silber

Note d'utilisation

LORO-XML Stahlabflussrohre muffenlos in DN 250 und DN 300, aus Stahl, feuerverzinkt. Für große Nennweiten hat LORO muffenlose Stahlabflusssysteme für die Regenentwässerung in DN 250 und DN 300 mit bauaufsichtlicher Zulassung Nr. Z-42.1-346 vom DIBt in sein Entwässerungsprogramm aufgenommen. Durch die Verwendung einer muffenlosen Verbindung wird die Verlegung mit einem CV-Verbinder für große Nennweiten wesentlich vereinfacht.

Téléchargements



Alles online

[Notice d'installation \(PDF\)](#)

[Certificat \(PDF\)](#)

[BIM IFC4 \(paramétrisch\)](#)

[Dessin dimensionnel \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Brochure \(PDF\)](#)

[CAD \(DWG\)](#)