LORO-X RAINWATER PIPE WITH REDUCED PIPE END

LORO-X pipe with Red.-plug connection 1500 mm DN 80

Descriere

LORO-X reducing push-fit rainfall downpipe, made of steel, hot-dip galvanized, round, without socket, with reduced pipe end, building material class A1, dimensionally stable, break-proof, 1500 mm, DN 80



Date articol

Cod EAN	**4038088005606**
Clasă ETIM	**EC011386**
Diametru nominal	**DN 80**
Lungime/grad nominal	**1500**
Dimensiuni exterioare (ÎxLxA)	**89 x 89 x 1560 mm**
Greutate	**5,40 Kg (STK)**
Grupă de produse	**1**
Număr tarif vamal	**73063012**
Material / Culoare	**Stahl feuerverzinkt, Silber**

Notă de utilizare

LORO-X Red.-Steck Regenfallrohre ohne Dichtelement bilden eine gradlinige Fallleitung vor der Fassade, ohne sichtbare Muffenverbindungen, insbesondere für die außenliegende Attikaentwässerung und vorgehängte Rundrinnen bzw. Kastenrinnen.Der Übergang von LORO-X Stahlabflussrohr oder von waagerechten Ablaufrohren von LORO-X Attikaabläufen erfolgt z.B. mit dem LORO-X Red.-Steck Anschlussstück.Als "senkrecht" wird eine Fallleitung bis zu einem Gefälle von 10 Grad zur waagerechten bzw. 180mm/m angegeben. Da Red.-Steck Verbindungen nicht rückstausicher sind, ist eine waagerechte Verlegung nicht zulässig.

Descărcări

Alles online

Instrucțiuni de montaj (PDF)
Desen CAD (PDF)
Broșură (PDF)
Certificat (PDF)
CAD 2D (DXF)
CAD (DWG)