

## LORO-X PIPE WITH 1 SOCKET 1500 MM DN 150

### LORO-X pipe 1 socket 1500 mm DN 150

#### Beskrivning

LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 1500 mm, + 1socket, DN150




#### Artikeldata

|                     |                             |
|---------------------|-----------------------------|
| EAN-kod             | 4038088005972               |
| ETIM-klass          | EC011386                    |
| Nominell diameter   | DN 150                      |
| Nominell längd/grad | 1500                        |
| Yttermått (HxBxL)   | 181 x 181 x 1580 mm         |
| Vikt                | 15,50 Kg (STK)              |
| Produktgrupp        | 1                           |
| Tullnummer          | 73063018                    |
| Material / Färg     | Stahl feuerverzinkt, Silber |

#### Användningsanvisning

Die Nenn-Länge (l) der Rohre wird ohne Länge der Muffe angegeben und kann daher zum Auszählen der Rohre in zusammengestecktem Zustand herangezogen werden. Beispiel: Nenn-Länge 1000 mm + 70 mm Muffe = 1070 mm Rohr-Außenmaß.



#### Nedladdningar



Alles online

[Monteringsanvisning \(PDF\)](#)
[Godkännande \(PDF\)](#)
[BIM IFC4 \(parametrisk\)](#)
[Måttitning \(PDF\)](#)
[CAD 2D \(DXF\)](#)
[BIM Revit \(RFA\)](#)
[Broschyr \(PDF\)](#)
[CAD \(DWG\)](#)