


LORO-X RAINWATER PIPE WITH REDUCED PIPE END

LORO-X pipe with red plug connection 500 mm DN 70

Description

LORO-X reducing push-fit rainfall downpipe, made of steel, hot-dip galvanized, round, without socket, with reduced pipe end, building material class A1, dimensionally stable, break-proof, 500 mm, DN70



Article information

EAN Code	4038088006023
ETIM Class	EC011386
Nominal diameter	DN 70
Nominal length/degree	500
Outside measurements (HxWxL)	73 x 73 x 560 mm
Weight	1,70 Kg (STK)
Product group	1
Customs tariff number	73063012
Material / Color	Stahl feuerverzinkt, Silber

Usage note

LORO-X Red.-Steck Regenfallrohre ohne Dichtelement bilden eine gradlinige Falleitung vor der Fassade, ohne sichtbare Muffenverbindungen, insbesondere für die außenliegende Attikaentwässerung und vorgehängte Rundrinnen bzw. Kastenrinnen. Der Übergang von LORO-X Stahlabflussrohr oder von waagerechten Ablaufrohren von LORO-X Attikaabläufen erfolgt z.B. mit dem LORO-X Red.-Steck Anschlussstück. Als "senkrecht" wird eine Falleitung bis zu einem Gefälle von 10 Grad zur waagerechten bzw. 180mm/m angegeben. Da Red.-Steck Verbindungen nicht rückstausicher sind, ist eine waagerechte Verlegung nicht zulässig.

Downloads



Alles online

[Installation \(PDF\)](#)

[Certificate \(PDF\)](#)

[CAD drawing \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Brochure \(PDF\)](#)

[CAD \(DWG\)](#)