


LORO-X RAINWATER PIPE WITH REDUCED PIPE END

LORO-X pipe with red plug connection 500 mm DN 70

Opis

LORO-X reducing push-fit rainfall downpipe, made of steel, hot-dip galvanized, round, without socket, with reduced pipe end, building material class A1, dimensionally stable, break-proof, 500 mm, DN70



Podatki o izdelku

EAN koda	4038088006023
ETIM razred	EC011386
Nazivni premer	DN 70
Nazivna dolžina/stopinja	500
Zunanje mere (VxŠxD)	73 x 73 x 560 mm
Teža	1,70 Kg (STK)
Skupina izdelkov	1
Carinska tarifna številka	73063012
Material / Barva	Stahl feuerverzinkt, Silber

Opomba za uporabo

LORO-X Red.-Steck Regenfallrohre ohne Dichtelement bilden eine gradlinige Falleitung vor der Fassade, ohne sichtbare Muffenverbindungen, insbesondere für die außenliegende Attikaentwässerung und vorgehängte Rundrinnen bzw. Kastenrinnen. Der Übergang von LORO-X Stahlabflussrohr oder von waagerechten Ablaufrohren von LORO-X Attikaabläufen erfolgt z.B. mit dem LORO-X Red.-Steck Anschlussstück. Als "senkrecht" wird eine Falleitung bis zu einem Gefälle von 10 Grad zur waagerechten bzw. 180mm/m angegeben. Da Red.-Steck Verbindungen nicht rückstausicher sind, ist eine waagerechte Verlegung nicht zulässig.

Prenosi



Alles online

[Navodila za vgradnjo \(PDF\)](#)
[Certifikat \(PDF\)](#)

[Merska risba \(PDF\)](#)
[CAD 2D \(DXF\)](#)

[Prospekt \(PDF\)](#)
[CAD \(DWG\)](#)