


LORO-X RAINWATER PIPE WITH REDUCED PIPE END

LORO-X pipe with red plug connection 500 mm DN 70

Descrizione

LORO-X reducing push-fit rainfall downpipe, made of steel, hot-dip galvanized, round, without socket, with reduced pipe end, building material class A1, dimensionally stable, break-proof, 500 mm, DN70



Dati articolo

Codice EAN	4038088006023
Classe ETIM	EC011386
Diametro nominale	DN 70
Lunghezza/grado nominale	500
Misure esterne (AxLxP)	73 x 73 x 560 mm
Peso	1,70 Kg (STK)
Gruppo prodotti	1
Numero tariffa doganale	73063012
Materiale / Colore	Stahl feuerverzinkt, Silber

Note d'uso

LORO-X Red.-Steck Regenfallrohre ohne Dichtelement bilden eine gradlinige Falleitung vor der Fassade, ohne sichtbare Muffenverbindungen, insbesondere für die außenliegende Attikaentwässerung und vorgehängte Rundrinnen bzw. Kastenrinnen. Der Übergang von LORO-X Stahlabflussrohr oder von waagerechten Ablaufrohren von LORO-X Attikaabläufen erfolgt z.B. mit dem LORO-X Red.-Steck Anschlussstück. Als "senkrecht" wird eine Falleitung bis zu einem Gefälle von 10 Grad zur waagerechten bzw. 180mm/m angegeben. Da Red.-Steck Verbindungen nicht rückstausicher sind, ist eine waagerechte Verlegung nicht zulässig.

Download



Alles online

[Istruzioni di installazione \(PDF\)](#)
[Certificato \(PDF\)](#)

[Disegno dimensionale \(PDF\)](#)
[CAD 2D \(DXF\)](#)

[Brochure \(PDF\)](#)
[CAD \(DWG\)](#)