

LORO-X DRAINJET SCUPPER EMERGENCY DRAIN, SIPHONIC FLOW, SERIES 62, WITHOUT ROOF PENETRATION, WITH BONDING FLANGE FOR

LORO-DRAINJET Attika emergency drain with adhesive flange for bitumen Height 40 mm Series 62 DN 50

Descripción

LORO-X DRAINJET siphonic parapet drain, series 62 without penetration into the roof, for emergency drainage with siphonic flow, discharge rate 8.5 l/s at 75 mm water level on the roof and 40 mm weir height, with bonding flange, 45-degree upstand for bituminous roofing sheets, roof penetration depth 0 mm, in accordance with DIN EN 1253, proof of performance with standard-compliant testing system with 4.2 m non-ventilated downpipe according to system data sheet LX1326, made of stainless steel, DN50




Datos del artículo

Código EAN	4038088083598
Clase ETIM	EC010400
Diámetro nominal	DN 50
Medidas exteriores (AxAxL)	290 x 897 x 215 mm
Peso	6,50 Kg (STK)
Grupo de productos	9
Número de arancel aduanero	73072980
Material / Color	Edelstahl, Silber

Nota de uso

LORO-DRAINJET® Attika-Notabläufe-ohne Eingriff ins Dach mit Klebeflansch, DN 50 und DN 70, für Bitumen-Dachabdichtungsbahnen



Descargas



Alles online

[Instrucciones de instalación \(PDF\)](#)

Certificado (PDF)

CAD (DWG)

[Dibujo dimensional \(PDF\)](#)

Ficha técnica del sistema LX 1326

[Folleto \(PDF\)](#)

CAD 2D (DXF)