
LORO-X DRAINJET SCUPPER EMERGENCY DRAIN, SIPHONIC FLOW, SERIES 62, WITHOUT ROOF PENETRATION, WITH BONDING FLANGE FOR

LORO-DRAINJET Attika emergency drain with adhesive flange for bitumen Weir height 50 mm Series 62 DN 70

Κείμενο προδιαγραφών

LORO-X DRAINJET siphonic parapet drain, series 62 without penetration into the roof, for emergency drainage with siphonic flow, discharge rate 14.5 l/s at 75 mm water level on the roof and 50 mm weir height, with bonding flange, 45-degree upstand for bituminous roofing sheets, roof penetration depth 0 mm, in accordance with DIN EN 1253, proof of performance with standard-compliant testing system with 4.2 m non-ventilated downpipe according to system data sheet LX637, made of stainless steel, DN70





Στοιχεία προϊόντος

Κωδικός EAN	**4038088083604**
Κατηγορία ETIM	**EC010400**
Ονομαστική διάμετρος	**DN 70**
Εξωτερικές διαστάσεις (ΥxΠxΜ)	**290 x 936 x 215 mm**
Βάρος	**6,80 Kg (STK)**
Ομάδα προϊόντων	**9**
Δασμολογικός αριθμός	**73072980**
Υλικό / Χρώμα	**Edelstahl, Silber**

Σημείωση χρήσης

LORO-DRAINJET® Attika-Notabläufe-ohne Eingriff ins Dach mit Klebeflansch, DN 50 und DN 70, für Bitumen-Dachabdichtungsbahnen

Λήψεις

Alles online

Οδηγίες εγκατάστασης (PDF)
Έγκριση (PDF)
CAD 3D (DWG)
Σχέδιο διαστάσεων (PDF)
Φύλλο δεδομένων συστήματος LX 637
CAD 3D (STEP)
Φυλλάδιο (PDF)
CAD 2D (DXF)
BIM 3D (IFC)