



LORO-X DRAINJET SCUPPER DRAIN, SIPHONIC FLOW, SERIES 62, WITHOUT ROOF PENETRATION, WITH CLAMPING FLANGE FOR BITUMINOUS

LORO-DRAINJET Attic drain with clamping flange for bitumen made of stainless steel series 62 DN 70

Beschrijving

LORO-X DRAINJET siphonic parapet drain, series 62 without penetration into the roof, for main drainage with siphonic flow, discharge rate 16.0 l/s at 55 mm water level on the roof, with clamping flange, as loose and fixed flange construction, 45-degree upstand for bituminous roofing sheets, roof penetration depth 0 mm, in accordance with DIN EN 1253, proof of performance with standard-compliant testing system with 4.2m non-ventilated downpipe according to system data sheet LX636, made of stainless steel, DN70



Artikelgegevens

EAN-code	4038088066096
ETIM Klasse	EC010400
Nominale diameter	DN 70
Buitenafmetingen (HxBxL)	270 x 927 x 192 mm
Gewicht	7,40 Kg (STK)
Productgroep	9
Douanetariefnummer	73072980

Materiaal / Kleur **Edelstahl, Silber**

Gebruiksaanwijzing

LORO-DRAINJET® Attika-Schnellabläufe-ohne Eingriff ins Dach, DN 50 und DN 70, für Bitumen-Dachabdichtungsbahnen

Downloads



Alles online

[Installatiehandleiding \(PDF\)](#)

[Certificaat \(PDF\)](#)

[CAD 3D \(DWG\)](#)

[Maattekening \(PDF\)](#)

[Systeemdatablad LX 636](#)

[BIM 3D \(STEP\)](#)

[Brochure \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)