
LORO-X DRAINJET SCUPPER DRAIN, SIPHONIC FLOW, SERIES 62, WITHOUT ROOF PENETRATION,WITH CLAMPING FLANGE FOR PLASTIC ROOFING

LORO-DRAINJET Attic drain with clamping flange for plastic 62 series DN 50

Texte de prescription

LORO-X DRAINJET siphonic parapet drain, series 62 without penetration into the roof, for main drainage with siphonic flow, discharge rate 7.0 l/s at 55 mm water level on the roof, with clamping flange, as loose and fixed flange construction, 90-degree upstand for plastic roofing sheets, roof penetration depth 0 mm, in accordance with DIN EN 1253, proof of performance with standard-compliant testing system with 4.2m non-ventilated downpipe according to system data sheet LX789, made of stainless steel, DN50





Données de l'article

Code EAN	**4038088083550**
Classe ETIM	**EC010400**
Diamètre nominal	**DN 50**
Dimensions extérieures (HxLxP)	**270 x 904 x 189 mm**
Poids	**6,50 Kg (STK)**
Groupe de produits	**9**
Numéro tarifaire douanier	**73072980**
Matériau / Couleur	**Edelstahl, Silber**

Note d'utilisation

LORO-DRAINJET® Attika-Schnellabläufe-ohne Eingriff ins Dach, DN 50 und DN 70, für Kunststoff-Dachabdichtungsbahnen

Téléchargements

Alles online

Notice d'installation (PDF)
Certificat (PDF)
CAD 3D (DWG)
Dessin dimensionnel (PDF)
Fiche technique du système LX 789
BIM 3D (STEP)
Brochure (PDF)
CAD 2D (DXF)
BIM 3D (IFC)