

LORO-X DRAINJET SCUPPER EMERGENCY DRAIN, SIPHONIC FLOW, SERIES 62, WITHOUT ROOF PENETRATION, WITH CLAMPING FLANGE FOR

LORO-DRAINJET ATTIKA Emergency drain with clamping flange for bitumen Weir height 40 mm Series 62 DN 50

Descrição

LORO-X DRAINJET siphonic parapet drain, series 62 without penetration into the roof, for emergency drainage with siphonic flow, discharge rate 8.5 l/s at 75 mm water level on the roof and 40 mm weir height, with clamping flange, as loose and fixed flange construction, 45-degree upstand for bituminous roofing sheets, roof penetration depth 0 mm, in accordance with DIN EN 1253, proof of performance with standard-compliant testing system with 4.2m non-ventilated downpipe according to system data sheet LX1326, made of stainless steel. DN50




Dados do artigo

Código EAN	4038088083543
Classe ETIM	EC010400
Diâmetro nominal	DN 50
Medidas exteriores (AxLxP)	270 x 926 x 192 mm
Peso	7,10 Kg (STK)
Grupo de produtos	9
Número de pauta aduaneira	73072980
Material / Cor	Edelstahl, Silber

Nota de utilização

LORO-DRAINJET® Attika-Notabläufe-ohne Eingriff ins Dach, DN 50 und DN 70, für Bitumen-Dachabdichtungsbahnen



Transferências



Alles online

[Instruções de instalação \(PDF\)](#)

Homologação (PDF)

CAD (DWG)

[Desenho cotado \(PDF\)](#)

Ficha técnica do sistema LX 1326

[Brochura \(PDF\)](#)

CAD 2D (DXF)