



LORO-X DRAINJET EMERGENCY SCUPPER DRAIN, SIPHONIC FLOW, SERIES 62, WITHOUT ROOF PENETRATION, WITH CLAMPING FLANGE FOR

LORO-DRAINJET ATTIKA Emergency drain with clamping flange for plastic, height 50 m Series 62 DN 70

Description

LORO-X DRAINJET siphonic parapet drain, series 62 without penetration into the roof, for emergency drainage with siphonic flow, discharge rate 14.5 l/s at 75 mm water level on the roof and 50 mm weir height, with clamping flange, as loose and fixed flange construction, 90-degree upstand for plastic roofing sheets, roof penetration depth 0 mm, in accordance with DIN EN 1253, proof of performance with standard-compliant testing system with 4.2m non-ventilated downpipe according to system data sheet LX637, made of stainless steel, DN70



Article information

EAN Code	4038088066188
ETIM Class	EC010400
Nominal diameter	DN 70
Outside measurements (HxWxL)	270 x 878 x 188 mm
Weight	7,90 Kg (STK)
Product group	9
Customs tariff number	73072980
Material / Color	Edelstahl, Silber

Usage note

LORO-DRAINJET® Attika-Notabläufe-ohne Eingriff ins Dach, DN 50 und DN 70, für Kunststoff-Dachabdichtungsbahnen

Downloads



Alles online

[Installation \(PDF\)](#)

[Certificate \(PDF\)](#)

CAD 3D (DWG)

[CAD drawing \(PDF\)](#)

System data sheet LX 637

BIM 3D (STEP)

[Brochure \(PDF\)](#)

CAD 2D (DXF)

BIM 3D (IFC)