



LORO-X DRAINJET EMERGENCY SCUPPER DRAIN, SIPHONIC FLOW, SERIES 62, WITHOUT ROOF PENETRATION, WITH CLAMPING FLANGE FOR

LORO-DRAINJET ATTIKA Emergency drain with clamping flange for plastic, height 50 m Series 62 DN 70

Beschrijving

LORO-X DRAINJET siphonic parapet drain, series 62 without penetration into the roof, for emergency drainage with siphonic flow, discharge rate 14.5 l/s at 75 mm water level on the roof and 50 mm weir height, with clamping flange, as loose and fixed flange construction, 90-degree upstand for plastic roofing sheets, roof penetration depth 0 mm, in accordance with DIN EN 1253, proof of performance with standard-compliant testing system with 4.2m non-ventilated downpipe according to system data sheet LX637, made of stainless steel, DN70



Artikelgegevens

EAN-code	4038088066188
ETIM Klasse	EC010400
Nominale diameter	DN 70
Buitenafmetingen (HxBxL)	270 x 878 x 188 mm
Gewicht	7,90 Kg (STK)
Productgroep	9
Douanetariefnumme r	73072980

Materiaal / Kleur	Edelstahl, Silber
-------------------	-------------------

Gebruiksaanwijzing

LORO-DRAINJET® Attika-Notabläufe-ohne Eingriff ins Dach, DN 50 und DN 70, für Kunststoff-Dachabdichtungsbahnen

Downloads



Alles online

[Installatiehandleiding \(PDF\)](#)

[Certificaat \(PDF\)](#)

CAD 3D (DWG)

[Maattekening \(PDF\)](#)

Systemdatablad LX 637

BIM 3D (STEP)

[Brochure \(PDF\)](#)

CAD 2D (DXF)

BIM 3D (IFC)