


LORO-X RAINSTAR SCUPPER EMERGENCY DRAIN, SIPHONIC FLOW, WITH CLAMPING FLANGE, WITH CUT-OUT DEPTH OF 50 MM FOR PLASTIC ROOFING

LORO-RAINSTAR Attika emergency drain stainless steel 55 mm installation depth clamping flange for plastic pressure pipe DN70

Beskrivelse

LORO-X RAINSTAR siphonic parapet drain, series 89 with low penetration depth, for emergency drainage with siphonic flow, discharge rate 17.6 l/s at 75 mm water level on the roof, with clamping flange, as loose and fixed flange construction, 90-degree upstand for plastic roofing sheets, roof penetration depth 55 mm, with DRAINJET hood made of stainless steel, according to DIN EN 1253, proof of performance with standard-compliant testing system with 4.2 m non-ventilated downpipe according to system data sheet LX798, made of stainless steel, DN70



Artikkeldata

EAN-kode	4038088074800
ETIM-klasse	EC010400
Nominell diameter	DN 70
Utvendige mål (HxBxL)	270 x 737 x 214 mm
Vekt	5,90 Kg (STK)
Produktgruppe	9
Tolltariffnummer	73072980
Materiale / Farge	Edelstahl, Silber

Bruksanvisning

LORO-X Rainstar® Attikaentwässerungssysteme mit geringer Eingrifftiefe von nur 55mm und vorgefertigter Attika-Aufkantung mit Klemm- oder Klebeflansch. Die Aufkantung der Rainstar Attikaentwässerungssysteme bietet als Montagehilfe in der Attika zusätzlichen Halt und verkürzt die Montagezeit. Abgedichtet wird der LORO-X Rainstar jedoch nur auf der horizontalen Ebene, sodass eine Abdichtung in der Aufkantung nicht notwendig ist. Die LORO-X RAINSTAR® Systeme gibt es auch als Serie 79 mit höher Freispiegel-Abflussleistung durch patentiertes, tiefergelegtes Rohr! Vorteile: -nur eine horizontale Abdichtungsebene -Aufkantung als Montagehilfe in der Attika -bis 21,7 l/s als Notentwässerung mit Druckströmung bei 75mm -geringe Eingrifftiefe von nur 55mm (Serie 89)

Nedlastinger



Alles online

[Monteringsanvisning \(PDF\)](#)
[Godkjenning \(PDF\)](#)
[CAD \(DWG\)](#)
[Måltegning \(PDF\)](#)
[Systemdatablad LX 798](#)
[BIM Revit \(RFA\)](#)
[Brosjyre \(PDF\)](#)
[CAD 2D \(DXF\)](#)