

LORO-X PIPE WITH 1 SOCKET 250 MM DN 125

LORO-X pipe 1 socket 250 mm DN 125

Popis

LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 250 mm + 1socket, DN125




Údaje o artiklu

EAN kód	4038088007075
ETIM třída	EC011386
Jmenovitý průměr	DN 125
Jmenovitá délka/stupeň	250
Vnější rozměry (VxŠxD)	152 x 152 x 325 mm
Hmotnost	2,70 Kg (STK)
Skupina produktů	1
Celní sazebník	73063018
Materiál / Barva	Stahl feuerverzinkt, Silber

Pokyny k použití

Die Nenn-Länge (l) der Rohre wird ohne Länge der Muffe angegeben und kann daher zum Auszählen der Rohre in zusammengestecktem Zustand herangezogen werden. Beispiel: Nenn-Länge 1000 mm + 70 mm Muffe = 1070 mm Rohr-Außenmaß.



Ke stažení



Alles online

[Návod k instalaci \(PDF\)](#)
[Certifikát \(PDF\)](#)
[BIM IFC4 \(parametrisch\)](#)

[Výkres rozměrů \(PDF\)](#)
[CAD 2D \(DXF\)](#)
[BIM Revit \(RFA\)](#)

[Prospekt \(PDF\)](#)
[CAD \(DWG\)](#)