

LORO-X RED.-ABZWEIG M.STECK-VERB.

LORO-X reduced branch with red plug connection DN 70/50

Opis

LORO-X reducing push-fit reducing branch, made of steel, hot-dip galvanized, with socket, with reduced pipe end, building material class A1, dimensionally stable, break-proof, 87 degrees, DN70/50




Podaci o artiklu

EAN kod	4038088061749
ETIM klasa	EC003025
Nazivni promjer	DN 70, DN 50
Nazivna duljina/stupanj	87
Vanjske mjere (VxŠxD)	73 x 103 x 320 mm
Težina	1,10 Kg (STK)
Grupa proizvoda	1
Carinski tarifni broj	73089098
Materijal / Boja	Stahl feuerverzinkt, Silber

Napomena za upotrebu

LORO-X Red.-Steck Red.-Abzweige ermöglichen das wasserdichte, seitliche Einleiten eines LORO-X Stahlabflussrohres (Muffe) mit einer kleineren Nennweite in eine Red.-Steck Fallleitung (reduziertes Einschubende) mit einer größeren Nennweite.



Preuzimanja



Alles online

[Upute za ugradnju \(PDF\)](#)

[Certifikat \(PDF\)](#)

[Dimenzijski crtež \(PDF\)](#)

[CAD \(DWG\)](#)

[Prospekt \(PDF\)](#)

[BIM IFC4 \(parametrisch\)](#)