LORO-X BRANCH WITHOUT SOCKET 0 DEGREE DN 250/250

LORO-X branch 45 degrees socketless DN 250/250

Opis

LORO-XML branch, made of steel, hot-dip galvanized, without socket, according to DIN EN 1123, with raised quality standard, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, approval no. Z-42.1-346 from DIBt, 45 degrees, DN250/250



Podatki o izdelku

EAN koda	**4038088068069**
ETIM razred	**EC003025**
Nazivni premer	**DN 250, DN 250**
Zunanje mere (VxŠxD)	**273 x 537 x 575 mm**
Teža	**14,50 Kg (STK)**
Skupina izdelkov	**1**
Carinska tarifna številka	**73089098**
Material / Barva	**Stahl feuerverzinkt, Silber**

Opomba za uporabo

LORO-XML Stahlabflussrohre muffenlos in DN 250 und DN 300, aus Stahl, feuerverzinkt.Für große Nennweiten hat LORO muffenlose Stahlabflussrohrsysteme für die Regenentwässerung in DN 250 und DN 300 mit bauaufsichtlicher Zulassung Nr. Z-42.1-346 vom DIBt in sein Entwässerungsprogramm aufgenommen.Durch die Verwendung einer muffenlosen Verbindung wird die Verlegung mit einem CV-Verbinder für große Nennweiten wesentlich vereinfacht.

Prenosi

Alles online

[Navodila za vgradnjo (PDF)]
[Certifikat (PDF)]
[BIM IFC4 (parametrisch)]
[Merska risba (PDF)]
[CAD 2D (DXF)]
[Prospekt (PDF)]
[CAD (DWG)]