LORO-X BOGEN MUFFENL.O.IBESCH.88GR.DN250

LORO-X bend 88 degrees socketless without internal coating 88 degree DN 250

Beskrivningstext

LORO-XML bend, made of steel, hot-dip galvanized, without socket, according to DIN EN 1123, with raised quality standard, building material class A1, dimensionally stable, break-proof, backflow-safe, approval no. Z-42.1-346 from DIBt, 88 degrees, without internal coating,DN250



Artikeldata

EAN-kod	4038088109892
ETIM-klass	EC003024
Nominell diameter	DN 250
Nominell längd/grad	88
Yttermått (HxBxL)	273 x 382 x 382 mm
Vikt	9,30 Kg (STK)
Produktgrupp	1
Tullnummer	73063012
Material / Färg	Stahl feuerverzinkt, Silber

Användningsanvisning

LORO-XML Stahlabflussrohre muffenlos in DN 250 und DN 300, aus Stahl, feuerverzinkt.Für große Nennweiten hat LORO muffenlose Stahlabflussrohrsysteme für die Regenentwässerung in DN 250 und DN 300 mit bauaufsichtlicher Zulassung Nr. Z-42.1-346 vom DIBt in sein Entwässerungsprogramm aufgenommen.Durch die Verwendung einer muffenlosen Verbindung wird die Verlegung mit einem CV-Verbinder für große Nennweiten wesentlich vereinfacht.

Nedladdningar

Alles online

Monteringsanvisning (PDF)
Godkännande (PDF)
BIM 3D (STEP)
Måttritning (PDF)
CAD 2D (DXF)
BIM IFC4 (parametrisch)
Broschyr (PDF)
CAD 3D (DWG)
BIM 3D (IFC)