

LORO-X BEND WITHOUT SOCKET 88 DEGREE DN 250

LORO-X bend 88 degrees socketless DN 250

Περιγραφή

LORO-XML bend, made of steel, hot-dip galvanized, without socket, according to DIN EN 1123, with raised quality standard, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, approval no. Z-42.1-346 from DIBt, 88 degrees, DN250




Στοιχεία προϊόντος

Κωδικός EAN	4038088069134
Κατηγορία ETIM	EC003024
Ονομαστική διάμετρος	DN 250
Ονομαστικό μήκος/μोίρες	88
Εξωτερικές διαστάσεις (ΥxΠxΜ)	273 x 382 x 382 mm
Βάρος	9,30 Kg (STK)
Ομάδα προϊόντων	1
Δασμολογικός αριθμός	73089098
Υλικό / Χρώμα	Stahl feuerverzinkt, Silber

Σημείωση χρήσης

LORO-XML Stahlabflussrohre muffenlos in DN 250 und DN 300, aus Stahl, feuerverzinkt. Für große Nennweiten hat LORO muffenlose Stahlabflussrohrsysteme für die Regenentwässerung in DN 250 und DN 300 mit bauaufsichtlicher Zulassung Nr. Z-42.1-346 vom DIBt in sein Entwässerungsprogramm aufgenommen. Durch die Verwendung einer muffenlosen Verbindung wird die Verlegung mit einem CV-Verbinder für große Nennweiten wesentlich vereinfacht.



Λήψεις



Alles online

[Οδηγίες εγκατάστασης \(PDF\)](#)

[Έγκριση \(PDF\)](#)

[BIM IFC4 \(parametrisch\)](#)

[Σχέδιο διαστάσεων \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Φυλλάδιο \(PDF\)](#)

[CAD \(DWG\)](#)