

LORO-X BEND WITHOUT SOCKET 70 DEGREE DN 250

LORO-X bend 70 degrees socketless DN 250

Beskrivning

LORO-XML bend, made of steel, hot-dip galvanized, without socket, according to DIN EN 1123, with raised quality standard, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, approval no. Z-42.1-346 from DIBt, 70 degrees, DN250




Artikeldata

EAN-kod	4038088068175
ETIM-klass	EC003024
Nominell diameter	DN 250
Nominell längd/grad	70
Yttermått (HxBxL)	273 x 356 x 375 mm
Vikt	10,80 Kg (STK)
Produktgrupp	1
Tullnummer	73089098
Material / Färg	Stahl feuerverzinkt, Silber

Användningsanvisning

LORO-XML Stahlabflussrohre muffenlos in DN 250 und DN 300, aus Stahl, feuerverzinkt. Für große Nennweiten hat LORO muffenlose Stahlabflussrohrsysteme für die Regenentwässerung in DN 250 und DN 300 mit bauaufsichtlicher Zulassung Nr. Z-42.1-346 vom DIBt in sein Entwässerungsprogramm aufgenommen. Durch die Verwendung einer muffenlosen Verbindung wird die Verlegung mit einem CV-Verbinder für große Nennweiten wesentlich vereinfacht.



Nedladdningar



Alles online

[Monteringsanvisning \(PDF\)](#)

[Godkännande \(PDF\)](#)

[BIM IFC4 \(parametrisk\)](#)

[Måttitning \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Broschyr \(PDF\)](#)

[CAD \(DWG\)](#)