

LORO-X BEND WITHOUT SOCKET 70 DEGREE DN 250

LORO-X bend 70 degrees socketless DN 250

Descriere

LORO-XML bend, made of steel, hot-dip galvanized, without socket, according to DIN EN 1123, with raised quality standard, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, approval no. Z-42.1-346 from DIBt, 70 degrees, DN250




Date articol

Cod EAN	4038088068175
Clasă ETIM	EC003024
Diametru nominal	DN 250
Lungime/grad nominal	70
Dimensiuni exterioare (îxLxA)	273 x 356 x 375 mm
Greutate	10,80 Kg (STK)
Grupă de produse	1
Număr tarif vamal	73089098
Material / Culoare	Stahl feuerverzinkt, Silber

Notă de utilizare

LORO-XML Stahlabflussrohre muffenlos in DN 250 und DN 300, aus Stahl, feuerverzinkt. Für große Nennweiten hat LORO muffenlose Stahlabflusssysteme für die Regenentwässerung in DN 250 und DN 300 mit bauaufsichtlicher Zulassung Nr. Z-42.1-346 vom DIBt in sein Entwässerungsprogramm aufgenommen. Durch die Verwendung einer muffenlosen Verbindung wird die Verlegung mit einem CV-Verbinder für große Nennweiten wesentlich vereinfacht.



Descărcări



Alles online

[Instrucțiuni de montaj \(PDF\)](#)

[Certificat \(PDF\)](#)

[BIM IFC4 \(parametric\)](#)

[Desen CAD \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Broșură \(PDF\)](#)

[CAD \(DWG\)](#)