

LORO-X BEND WITHOUT SOCKET 30 DEGREE DN 300

LORO-X bend 30 degrees socketless DN 300

Описание

LORO-XML bend, made of steel, hot-dip galvanized, without socket, according to DIN EN 1123, with raised quality standard, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, approval no. Z-42.1-346 from DIBt, 30 degrees, DN300




Данни за артикула

EAN код	4038088069165
ETIM клас	EC003024
Номинален диаметър	DN 300
Номинална дължина/градус	30
Външни размери (ВxШxД)	324 x 369 x 331 mm
Тегло	9,30 Kg (STK)
Продуктова група	1
Митнически тарифен номер	73089098
Материал / Цвят	Stahl feuerverzinkt, Silber

Забележка за употреба

LORO-XML Stahlabflussrohre muffenlos in DN 250 und DN 300, aus Stahl, feuerverzinkt. Für große Nennweiten hat LORO muffenlose Stahlabflussrohrsysteme für die Regenentwässerung in DN 250 und DN 300 mit bauaufsichtlicher Zulassung Nr. Z-42.1-346 vom DIBt in sein Entwässerungsprogramm aufgenommen. Durch die Verwendung einer muffenlosen Verbindung wird die Verlegung mit einem CV-Verbinder für große Nennweiten wesentlich vereinfacht.



Изтегляния



Alles online

[Инструкция за монтаж \(PDF\)](#)

[Сертификат \(PDF\)](#)

[BIM IFC4 \(parametrisch\)](#)

[CAD чертеж \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Брошура \(PDF\)](#)

[CAD \(DWG\)](#)