LORO-X BEND WITHOUT SOCKET 30 DEGREE DN 300

LORO-X bend 30 degrees socketless DN 300

Opis

LORO-XML bend, made of steel, hot-dip galvanized, without socket, according to DIN EN 1123, with raised quality standard, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, approval no. Z-42.1-346 from DIBt, 30 degrees, DN300



Podaci o artiklu

EAN kod	4038088069165
ETIM klasa	EC003024
Nazivni promjer	DN 300
Nazivna duljina/stupanj	30
Vanjske mjere (VxŠxD)	324 x 369 x 331 mm
Težina	9,30 Kg (STK)
Grupa proizvoda	1
Carinski tarifni broj	73089098
Materijal / Boja	Stahl feuerverzinkt, Silber

Napomena za upotrebu

LORO-XML Stahlabflussrohre muffenlos in DN 250 und DN 300, aus Stahl, feuerverzinkt.Für große Nennweiten hat LORO muffenlose Stahlabflussrohrsysteme für die Regenentwässerung in DN 250 und DN 300 mit bauaufsichtlicher Zulassung Nr. Z-42.1-346 vom DIBt in sein Entwässerungsprogramm aufgenommen.Durch die Verwendung einer muffenlosen Verbindung wird die Verlegung mit einem CV-Verbinder für große Nennweiten wesentlich vereinfacht.

Preuzimanja

Alles online

- Upute za ugradnju (PDF)
- Certifikat (PDF)
- BIM IFC4 (parametrisch)
- Dimenzijski crtež (PDF)
- CAD 2D (DXF)
- Prospekt (PDF)
- CAD (DWG)