

LORO-X BEND WITHOUT SOCKET 15 DEGREE DN 300

LORO-X bend 15 degrees socketless DN 300

Leírás

LORO-XML bend, made of steel, hot-dip galvanized, without socket, according to DIN EN 1123, with raised quality standard, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, approval no. Z-42.1-346 from DIBt, 15 degrees, DN300




Cikkadatok

EAN kód	4038088069189
ETIM osztály	EC003024
Névleges átmérő	DN 300
Névleges hossz/fok	15
Külső méretek (MxSzxH)	324 x 347 x 262 mm
Súly	7,80 Kg (STK)
Termékcsoport	1
Vámtarifaszám	73089098
Anyag / Szín	Stahl feuerverzinkt, Silber

Használati megjegyzés

LORO-XML Stahlabflussrohre muffenlos in DN 250 und DN 300, aus Stahl, feuerverzinkt. Für große Nennweiten hat LORO muffenlose Stahlabflussrohrsysteme für die Regenentwässerung in DN 250 und DN 300 mit bauaufsichtlicher Zulassung Nr. Z-42.1-346 vom DIBt in sein Entwässerungsprogramm aufgenommen. Durch die Verwendung einer muffenlosen Verbindung wird die Verlegung mit einem CV-Verbinder für große Nennweiten wesentlich vereinfacht.



Letöltések



Alles online

[Szerelési útmutató \(PDF\)](#)
[Engedély \(PDF\)](#)
[BIM IFC4 \(parametrisch\)](#)

[Méterrajz \(PDF\)](#)
[CAD 2D \(DXF\)](#)

[Prospektus \(PDF\)](#)
[CAD \(DWG\)](#)