

LORO-X TRANSITION PIPE CONCENTRIC, DN 200/250

I=SOCKET, II=WITHOUT SOCKET
LORO-X transition pipe socketless / socket DN 200/250

Opis

LORO-XML transition pipe, made of steel, hot-dip galvanized, from LORO-X pipe with socket to LORO-XML pipe without socket, concentric, according to DIN EN 1123, with raised quality standard, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, approval no. Z-42.1-346 from DIBt, DN200/250




Podaci o artiklu

EAN kod	4038088068250
ETIM klasa	EC003024
Nazivni promjer	DN 200, DN 250
Vanjske mjere (VxŠxD)	273 x 273 x 259 mm
Težina	5,90 Kg (STK)
Grupa proizvoda	1
Carinski tarifni broj	73089098
Materijal / Boja	Stahl feuerverzinkt, Silber

Napomena za upotrebu

LORO-XML Stahlabflussrohre muffenlos in DN 200 und DN 250, aus Stahl, feuerverzinkt. Für große Nennweiten hat LORO muffenlose Stahlabflusssysteme für die Regenentwässerung in DN 250 und DN 300 mit bauaufsichtlicher Zulassung Nr. Z-42.1-346 vom DIBt in sein Entwässerungsprogramm aufgenommen. Durch die Verwendung einer muffenlosen Verbindung wird die Verlegung mit einem CV-Verbinder für große Nennweiten wesentlich vereinfacht.



Preuzimanja



Alles online

[Upute za ugradnju \(PDF\)](#)
[Certifikat \(PDF\)](#)
[Dimenzijski crtež \(PDF\)](#)
[CAD 2D \(DXF\)](#)
[Prospekt \(PDF\)](#)
[CAD \(DWG\)](#)