

LORO-X TRANSITION PIPE CONCENTRIC, DN 200/250

I=SOCKET, II=WITHOUT SOCKET

LORO-X transition pipe socketless / socket DN 200/250

Descrizione

LORO-XML transition pipe, made of steel, hot-dip galvanized, from LORO-X pipe with socket to LORO-XML pipe without socket, concentric, according to DIN EN 1123, with raised quality standard, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, approval no. Z-42.1-346 from DIBt, DN200/250




Dati articolo

Codice EAN	4038088068250
Classe ETIM	EC003024
Diametro nominale	DN 200, DN 250
Misure esterne (AxLxP)	273 x 273 x 259 mm
Peso	5,90 Kg (STK)
Gruppo prodotti	1
Numero tariffa doganale	73089098
Materiale / Colore	Stahl feuerverzinkt, Silber

Note d'uso

LORO-XML Stahlabflussrohre muffenlos in DN 200 und DN 250, aus Stahl, feuerverzinkt. Für große Nennweiten hat LORO muffenlose Stahlabflusssysteme für die Regenentwässerung in DN 250 und DN 300 mit bauaufsichtlicher Zulassung Nr. Z-42.1-346 vom DIBt in sein Entwässerungsprogramm aufgenommen. Durch die Verwendung einer muffenlosen Verbindung wird die Verlegung mit einem CV-Verbinder für große Nennweiten wesentlich vereinfacht.



Download



Alles online

[Istruzioni di installazione \(PDF\)](#)
[Certificato \(PDF\)](#)

[Disegno dimensionale \(PDF\)](#)
[CAD 2D \(DXF\)](#)

[Brochure \(PDF\)](#)
[CAD \(DWG\)](#)