

LX-ANSCHLUSSSTÜCK DN80 M. KURZMUFFE UND

LORO-X connection piece with short socket and reduced insertion end DN 80

Descrizione

LORO-X connector made of steel, hot-dip galvanized, with short socket and reduced insertion end, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, DN80




Dati articolo

Codice EAN	4038088109243
Classe ETIM	EC011386
Diametro nominale	DN 80
Misure esterne (AxLxP)	103 x 103 x 115 mm
Peso	0,40 Kg (STK)
Gruppo prodotti	1
Numero tariffa doganale	73063012
Materiale / Colore	Stahl feuerverzinkt, Silber

Note d'uso

kein Verwendungshinweis notwendig



Download



Alles online

[Istruzioni di installazione \(PDF\)](#)

[Certificato \(PDF\)](#)

[BIM 3D \(STEP\)](#)

[Disegno dimensionale \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)

[Brochure \(PDF\)](#)

[CAD 3D \(DWG\)](#)