

LX-ANSCHLUSSSTÜCK DN100 M.KURZMUFFE UND

LORO-X connection piece with short socket and reduced insertion end DN 100

Beskrivelse

LORO-X connector made of steel, hot-dip galvanized, with short socket and reduced insertion end, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, DN100




Artikkeldata

EAN-kode	4038088109250
ETIM-klasse	EC011386
Nominell diameter	DN 100
Utvendige mål (HxBxL)	118 x 118 x 155 mm
Vekt	0,60 Kg (STK)
Produktgruppe	1
Tolltariffnummer	73063012
Materiale / Farge	Stahl feuerverzinkt, Silber

Bruksanvisning

kein Verwendungshinweis notwendig



Nedlastinger



Alles online

[Monteringsanvisning \(PDF\)](#)

[Godkjenning \(PDF\)](#)

[BIM 3D \(IFC\)](#)

[Måltegning \(PDF\)](#)

[CAD 3D \(DWG\)](#)

[Brosjyre \(PDF\)](#)

[BIM 3D \(STEP\)](#)