



LX-SPEIER 1+2 STUFE M.KLEBEFL.Z.BAUS.AB

LORO-X VARIO upstand spout with adhesive flange for bending on site with double pipe DN 70 made of stainless steel 1.4301

Beskrivelse

LORO-X VARIO Upstand spout with double pipe 1 step socket and on-site bendable bonding flange, for emergency drainage with gravity flow, with variable weir height, proof of performance according to specification sheet LX3005, made of stainless steel, material no. 1.4301, DN70



Artikkeldata

EAN-kode	4038088108666
ETIM-klasse	EC010400
Nominell diameter	DN 70
Nominell lengde/grad	400
Utvendige mål (HxBxL)	400 x 540 x 400 mm
Vekt	3,40 Kg (STK)
Produktgruppe	9
Tolltariffnummer	73072980
Materiale / Farge	Edelstahl, Silber

Bruksanvisning

LORO-X VARIO Kant Speier zum bauseitigen Abkanten eignen sich insbesondere zur Notentwässerung von Balkonen, Terrassen oder kleinen Dachflächen. Der Edelstahl-Klebeflansch lässt sich mit handelsüblichen Werkzeugen abkanten, so dass die Höhe der Notentwässerung variabel und stufenlos einstellbar ist. Der passende Siebkorb verhindert, dass Gegenstände durch den Speier ungewollt ins Freie gelangen können.

Nedlastinger



Alles online

[Monteringsanvisning \(PDF\)](#)

[Godkjenning \(PDF\)](#)

[BIM 3D \(STEP\)](#)

[Måltegning \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)

[Brosjyre \(PDF\)](#)

[CAD 3D \(DWG\)](#)