


LX UMLENKUNG M.FEST-U.LOSFLANSCH F.KUNST

LORO-X baffle with fixed and loose flange DN 100/50

Opis

LORO-X DUOSTREAM transition from downpipe DN100 into offset via roof terrace DN100/DN 50, for LORO-X cascade drainage, for the installation of the collector pipe within the insulation layer, made of steel, hot-dip galvanized, DN100/50




Podatki o izdelku

EAN koda	4038088100752
ETIM razred	EC003024
Nazivni premer	DN 100, DN 50
Zunanje mere (VxŠxD)	200 x 270 x 670 mm
Teža	6,40 Kg (STK)
Skupina izdelkov	9
Carinska tarifna številka	73089098
Material / Barva	Stahl feuerverzinkt, Silber

Opomba za uporabo

kein Verwendungshinweis notwendig



Prenosi



Alles online

[Navodila za vgradnjo \(PDF\)](#)

[Certifikat \(PDF\)](#)

[CAD 3D \(DWG\)](#)

[Merska risba \(PDF\)](#)

[Podatkovni list sistema LX 3012](#)

[BIM 3D \(STEP\)](#)

[Prospekt \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)