


LX KASKADENDURCHF.SR.43,RIR,HPT.,FRSP.,

LORO-X cascade duct for pipe in pipe with adhesive flange for bitumen DN 100/50

Popis

LORO-X DUOSTREAM cascade drainage main drain for roof terraces, series 43, Attika-Direct, pipe-in-pipe, for main drainage with gravity flow, discharge rate 2.0 l/sec with a water height of 35 mm on the roof terrace, with bonding flange, 45-degree for bitumen roofing sheets, proof of performance according to specification sheet LX1981, made of stainless steel, DN100/50



Údaje o artikli

EAN kód	4038088102152
ETIM trieda	EC011350
Menovitý priemer	DN 100, DN 50
Vonkajšie rozmery (VxŠxH)	380 x 735 x 270 mm
Hmotnosť	8,80 Kg (STK)
Skupina produktov	9
Colný sadzobník	73072980
Materiál / Farba	Edelstahl, Silber

Pokyny na použitie

kein Verwendungshinweis notwendig

Na stiahnutie



Alles online

[Návod na montáž \(PDF\)](#)

[Systémový dátový list LX 1981](#)

[BIM 3D \(STEP\)](#)

[Rozmerový výkres \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)

[Prospekt \(PDF\)](#)

[CAD 3D \(DWG\)](#)