

LX KASKADENDURCHF.SR.43,RIR,HPT.,FRSP.,

LORO-X cascade duct for pipe in pipe with adhesive flange for bitumen DN 100/50

Beskrivelse

LORO-X DUOSTREAM cascade drainage main drain for roof terraces, series 43, Attika-Direct, pipe-in-pipe, for main drainage with gravity flow, discharge rate 2.0 l/sec with a water height of 35 mm on the roof terrace, with bonding flange, 45-degree for bitumen roofing sheets, proof of performance according to specification sheet LX1981, made of stainless steel, DN100/50




Artikeldata

EAN-kode	4038088102152
ETIM Klasse	EC011350
Nominal diameter	DN 100, DN 50
Ydermål (HxBxL)	380 x 735 x 270 mm
Vægt	8,80 Kg (STK)
Produktgruppe	9
Toldtarifnummer	73072980
Materiale / Farve	Edelstahl, Silber

Brugsanvisning

kein Verwendungshinweis notwendig



Downloads



Alles online

[Installationsvejledning \(PDF\)](#)

[Systemdatablad LX 1981](#)

[BIM 3D \(STEP\)](#)

[Måltegning \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)

[Brochure \(PDF\)](#)

[CAD 3D \(DWG\)](#)