


LX KASKADENDURCHF.SR.43,RIR,HPT.,FRSP.,

LORO-X cascade passage series 43 for pipe-in-pipe main drainage gravity flow with adhesive flange for liquid plastic DN 100/50

Description

LORO-X DUOSTREAM cascade drainage main drain for roof terraces, series 43, Attika-Direct, pipe-in-pipe, for main drainage with gravity flow, discharge rate 2.0 l/sec with a water height of 35 mm on the roof terrace, with bonding flange, 90-degree for liquid plastic, proof of performance according to specification sheet LX1981, made of stainless steel, DN100/50




Données de l'article

Code EAN	4038088105108
Classe ETIM	EC004949
Diamètre nominal	DN 100, DN 50
Dimensions extérieures (HxLxP)	246 x 380 x 738 mm
Poids	8,90 Kg (STK)
Groupe de produits	9
Numéro tarifaire douanier	73072980
Matériau / Couleur	Edelstahl, Silber

Note d'utilisation

kein Verwendungshinweis notwendig



Téléchargements



Alles online

[Notice d'installation \(PDF\)](#)

[Fiche technique du système LX 1981](#)

[BIM 3D \(STEP\)](#)

[Dessin dimensionnel \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)

[Brochure \(PDF\)](#)

[CAD 3D \(DWG\)](#)