


LX KASKADENDURCHF.SR.43,RIR,HPT.,FRSP.,

LORO-X cascade penetration, Series 43, for pipe-in-pipe main drainage, free-flowing, with clamping flange for plastic roof sealing membranes DN 100/50

Beskrivning

LORO-X DUOSTREAM cascade drainage main drain for roof terraces, series 43, Attika-Direct, pipe-in-pipe, for main drainage with gravity flow, discharge rate 2.0 l/sec with a water height of 35 mm on the roof terrace, with clamping flange, 90-degree for plastic roofing sheets, proof of performance according to specification sheet LX1981, made of stainless steel, DN100/50




Artikeldata

EAN-kod	4038088106334
ETIM-klass	EC004949
Nominell diameter	DN 100, DN 50
Ytermått (HxBxL)	247 x 280 x 694 mm
Vikt	8,80 Kg (STK)
Produktgrupp	9
Tullnummer	73072980
Material / Färg	Edelstahl, Silber

Användningsanvisning

kein Verwendungshinweis notwendig



Nedladdningar



Alles online

[Måttitning \(PDF\)](#)
[Systemdatablad LX 1981](#)
[BIM 3D \(STEP\)](#)
[Broschyr \(PDF\)](#)
[CAD 2D \(DXF\)](#)
[BIM 3D \(IFC\)](#)
[Godkännande \(PDF\)](#)
[CAD 3D \(DWG\)](#)