



LX-HPT-NOT KOMBI ABL.SR.88,HPT.DRST/

LORO-RAINSTAR Main-Emergency-Combi Drain Main drain DN 100 Pressure flow Emergency drain DN 50 Pressure flow

Description

LORO-X main-emergency combination parapet drain, series 88 pipe-in-pipe, for main drainage with siphonic flow, discharge rate 7.5 l/s at 55 mm water level on the roof and emergency drainage with siphonic flow 7.5 l/s at 75 mm, with clamping flange, as loose and fixed flange construction, 45-degree upstand for bituminous and plastic roofing sheets, penetration depth 106 mm, with main-emergency combination cover made of stainless steel, according to DIN EN 1253, proof of performance with standard-compliant testing system with 4.2 m non-ventilated downpipe according to system data sheet LX1456, made of steel, hot-dip galvanized, DN100/50



Article information

EAN Code	4038088106723
ETIM Class	EC010400
Nominal diameter	DN 100
Outside measurements (HxWxL)	255 x 270 x 605 mm
Weight	12,20 Kg (STK)
Product group	9
Customs tariff number	73089098
Material / Color	Stahl feuerverzinkt, Silber

Usage note

LORO-X Haupt-Not-Kombi ist das Stichwort für die von LORO zum Patent angemeldete innovative Rohr-in-Rohr Lösung. Durch das patentierte Rohr-in-Rohr Prinzip von LORO ist es möglich, ein unabhängiges zweites Entwässerungssystem innerhalb nur einer einzigen sichtbaren Falleitung unterzubringen. Das LORO-X Modell Haupt-Not-Kombi Rohr-in-Rohr kombiniert eine Silent-Freispiegel-Hauptentwässerung (4,5 l/s bei 35 mm Wasserhöhe) mit einer zusätzlichen Silent Power-Notentwässerung (8,2 l/s bei 75 mm Wasserhöhe) in einem einzigen System. Vorteile: 2 in 1 : Integriertes Notentwässerungssystem, Nur 1 Durchbruch durch die Attika für die Haupt- und Notentwässerung. Nur 1 sichtbare Falleitung an der Fassade. Nur 1 Ablauf mit nur 1 Abdichtungsebene. Stille Freispiegelströmung bei Normalregen (Hauptentwässerung DN 100), Power Druckströmung bei Starkregen (Notentwässerung DN 50), Die Systemfunktion und die dachentwässerungsnormgerechte Leistung ist vom unabhängigen Prüfinstitut LGA gemessen und zertifiziert

Downloads



Alles online

[Installation \(PDF\)](#)

[Certificate \(PDF\)](#)

[CAD 3D \(DWG\)](#)

[CAD drawing \(PDF\)](#)

[System data sheet LX 1456](#)

[BIM 3D \(STEP\)](#)

[Brochure \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)