



LORO-ATTIKA-ABL.FREISP.F.UMKEHRD.M.KLEMM

LORO-Attika drain free-standing mirror installation inverted roof with clamping flange for PVC screen unit 210 mm DN 100

Kuvaus

LORO - RAINSTAR parapet drain for inverted roof, for gravity flow, according to DIN EN 1253, with 90 clamping flange, as loose and fixed flange construction, for plastic roofing sheets, made of stainless steel and strainer unit for inverted roof, for installation height 210 mm, consisting of strainer basket and strainer cover, made of stainless steel, DN100



Tuotetiedot

EAN-koodi	4038088093924
ETIM-luokka	EC011350
Nimellishalkaisija	DN 100
Ulkomitat (KxLxS)	270 x 738 x 341 mm
Paino	6,80 Kg (STK)
Tuoteryhmä	9
Tullitariffin numero	73072980
Materiaali / Väri	Edelstahl, Silber

Käyttöohje

LORO-X Serie 89 Attikaentwässerung mit hohem Siebkorb - und zusätzlich höhenvariablem Wehr bei der Notentwässerung eignet sich insbesondere für Umkehrdächer. Die unter der Wärmedämmung liegende Abdichtungsbahn wird in den unten angeordneten Ablaufkörper eingeklemmt. Die Höhe des Siebkorbes - und bei der Notentwässerung die Höhe des höhenvariablen Wehres - richtet sich nach der Höhe der Wärmedämmung und der darüber liegenden Bekiesung.

Lataukset



Alles online

[Asennusohje \(PDF\)](#)

Hvåksyntå (PDF)

BIM 3D (STEP)

[Mittapiirustus \(PDF\)](#)

CAD 2D (DXF)

BIM 3D (IFC)

[Esite \(PDF\)](#)

CAD 3D (DWG)