

LX RETENTIONS-DREHSCHIEBER, DN 100

LORO-X retention rotary valve DN 100

Beschrijving

LORO-X retention rotary slide, consisting of upper and lower part. Attention: the amount of retention discharge has to be installed and set according to specification sheet LX3035, made of stainless steel, DN 100




Artikelgegevens

EAN-code	4038088105306
ETIM Klasse	EC010917
Nominale diameter	DN 100
Buitenafmetingen (HxBxL)	223 x 110 x 110 mm
Gewicht	0,90 Kg (STK)
Productgroep	4
Douanetariefnummer	73072980

Materiaal / Kleur	Edelstahl, Silber
-------------------	-------------------

Gebruiksaanwijzing

LORO bietet für Hauptentwässerung mit Retention und Notentwässerung mit höhenvariablem Wehr aufeinander abgestimmte VARIOFIT Strömungshilfen, die objektbezogen berechnet und gefertigt werden. Die Höhe des Anstauelementes der Notentwässerung wird objektbezogen an die Retentionswasserhöhe der Hauptentwässerung mit Retention angepasst. Die aufgeführten Strömungshilfen passen auf die Grundkörper der angegebenen Serien der Flachdachentwässerung.



Downloads



Alles online

[Maattekening \(PDF\)](#)

BIM 3D (STEP)

CAD 2D (DXF)

BIM 3D (IFC)

CAD 3D (DWG)