


LX-RETENTIONS-DREHSCHIEBER F.F. DACHABL.

LORO-X retention rotary valve for flat roof series 84 DN 100

Description

LORO-X retention rotary slide, consisting of upper and lower part. Attention: the amount of retention discharge has to be installed and set, to fit flat roof drain body series 84 DN 100, made of stainless steel



Article information

EAN Code	4038088106747
ETIM Class	EC010917
Nominal diameter	DN 100
Outside measurements (HxWxL)	258 x 258 x 185 mm
Weight	1,10 Kg (STK)
Product group	9
Customs tariff number	73072980
Material / Color	Edelstahl, Silber

Usage note

LORO bietet für Hauptentwässerung mit Retention und Notentwässerung mit höhenvariablem Wehr aufeinander abgestimmte VARIOFIT Strömungshilfen, die objektbezogen berechnet und gefertigt werden. Die Höhe des Anstauerelementes der Notentwässerung wird objektbezogen an die Retentionswasserhöhe der Hauptentwässerung mit Retention angepasst. Die aufgeführten Strömungshilfen passen auf die Grundkörper der angegebenen Serien der Flachdachentwässerung.

Downloads



Alles online

[CAD drawing \(PDF\)](#)
[CAD 2D \(DXF\)](#)
[BIM 3D \(IFC\)](#)
[Brochure \(PDF\)](#)
[CAD 3D \(DWG\)](#)
[Aufbauschema \(PDF\)](#)
[BIM 3D \(STEP\)](#)