LX-RETENTIONSEINH.F.DL.SR.84,HPT.

LORO-X retention unit for DRAINLET DN 70 with retention openings according to specification including strainer basket 210 mm

Description

LORO-X VARIOFIT flow aid for retention roof drainage,building-related design, strainer basket 210 mm, please contact LOROWERK for the determination of the necessary retention openings, for the main drainage and height-adjustable retention pipe, to fit DRAINLET flat roof drain, series 84(DL) DN 70



Données de l'article

Code EAN	4038088101032
Classe ETIM	EC011398
Diamètre nominal	DN 70
Dimensions extérieures (HxLxP)	236 x 260 x 260 mm
Poids	3,20 Kg (STK)
Groupe de produits	9
Numéro tarifaire douanier	73072980
Matériau / Couleur	Edelstahl, Silber

Note d'utilisation

LORO bietet für Hauptentwässerung mit Retention und Notentwässerung mit höhenvariablem Wehr aufeinander abgestimmte VARIOFIT Strömungshilfen, die objektbezogen berechnet und gefertigt werden. Die Höhe des Anstauelementes der Notentwässerung wird objektbezogen an die Retentionswasserhöhe der Hauptentwässerung mit Retention angepasst. Die aufgeführten Strömungshilfen passen auf die Grundkörper der angegebenen Serien der Flachdachentwässerung.

Téléchargements

Alles online

Dessin dimensionnel (PDF)
Aufbauschema (PDF)
BIM 3D (STEP)
Brochure (PDF)
CAD 2D (DXF)
BIM 3D (IFC)
Certificat (PDF)
CAD 3D (DWG)