

LX-RETENTIONSEINH.F.DL.SR.84,HPT.

LORO-X retention unit for DRAINLET DN 100 with retention openings according to specification including strainer basket 210 mm

Beskrivning

LORO-X VARIOFIT flow aid for retention roof drainage, building-related design, strainer basket 210 mm, please contact LOROWERK for the determination of the necessary retention openings, for the main drainage and height-adjustable retention pipe, to fit DRAINLET flat roof drain, series 84(DL), DN 100




Artikeldata

EAN-kod	4038088100875
ETIM-klass	EC011398
Nominell diameter	DN 100
Yttermått (HxBxL)	236 x 290 x 290 mm
Vikt	3,60 Kg (STK)
Produktgrupp	9
Tullnummer	73072980
Material / Färg	Edelstahl, Silber

Användningsanvisning

LORO bietet für Hauptentwässerung mit Retention und Notentwässerung mit höhenvariablem Wehr aufeinander abgestimmte VARIOFIT Strömungshilfen, die objektbezogen berechnet und gefertigt werden. Die Höhe des Anstauelementes der Notentwässerung wird objektbezogen an die Retentionswasserhöhe der Hauptentwässerung mit Retention angepasst. Die aufgeführten Strömungshilfen passen auf die Grundkörper der angegebenen Serien der Flachdachentwässerung.



Nedladdningar



Alles online

[Mått ritning \(PDF\)](#)

[Aufbauschema \(PDF\)](#)

BIM 3D (STEP)

[Broschyr \(PDF\)](#)

CAD 2D (DXF)

BIM 3D (IFC)

[Godkännande \(PDF\)](#)

CAD 3D (DWG)