

LX-RETENTIONSEINH.F.DL.SR.84,NOT.

Specify LORO-X flange unit for DRAINLET emergency drainage with variable weir and DN125 strainer unit
Height

Description

LORO-X VARIOFIT flow aid, strainer basket 210 mm, building-related design please indicate desired weir height when ordering, for emergency drainage with gravity flow, variable weir height, to fit DRAINLET flat roof drain, series 84(DL), DN125




Article information

EAN Code	4038088101230
ETIM Class	EC011398
Nominal diameter	DN 125
Outside measurements (HxWxL)	236 x 320 x 320 mm
Weight	4,10 Kg (STK)
Product group	9
Customs tariff number	73072980
Material / Color	Edelstahl, Silber

Usage note

LORO bietet für Hauptentwässerung mit Retention und Notentwässerung mit höhenvariablem Wehr aufeinander abgestimmte VARIOFIT Strömungshilfen, die objektbezogen berechnet und gefertigt werden. Die Höhe des Anstauelementes der Notentwässerung wird objektbezogen an die Retentionswasserhöhe der Hauptentwässerung mit Retention angepasst. Die aufgeführten Strömungshilfen passen auf die Grundkörper der angegebenen Serien der Flachdachentwässerung.



Downloads



Alles online

[CAD drawing \(PDF\)](#)
[Aufbauschema \(PDF\)](#)
[BIM 3D \(STEP\)](#)

[Brochure \(PDF\)](#)
[CAD 2D \(DXF\)](#)
[BIM 3D \(IFC\)](#)

[Certificate \(PDF\)](#)
[CAD 3D \(DWG\)](#)