


LX-RETENTIONSEINH.F.DL.SR.84,NOT.

LORO-X retention unit for DRAINLET Series 84 emergency drainage with 500 mm strainer basket with variable weir to DN 100 specification

Opis

LORO-X VARIOFIT flow aid, strainer basket 500 mm, building-related design please indicate desired weir height when ordering, for emergency drainage with gravity flow, variable weir height, to fit DRAINLET flat roof drain, series 84(DL), DN 100



Dane artykułu

Kod EAN 4038088106709

Klasa ETIM EC010827

Średnica nominalna DN 100

Wymiary zewnętrzne 521 x 290 x 290 mm (WxSxD)

Waga 4,50 Kg (STK)


Grupa produktów 9

Numer taryfy celnej 73072980

Materiał / Kolor Edelstahl, Silber

Wskazówki dotyczące użytkowania

LORO bietet für Hauptentwässerung mit Retention und Notentwässerung mit höhenvariablem Wehr aufeinander abgestimmte VARIOFIT Strömungshilfen, die objektbezogen berechnet und gefertigt werden. Die Höhe des Anstauelementes der Notentwässerung wird objektbezogen an die Retentionswasserhöhe der Hauptentwässerung mit Retention angepasst. Die aufgeführten Strömungshilfen passen auf die Grundkörper der angegebenen Serien der Flachdachentwässerung.



Pobieranie



Alles online

[Rysunek wymiarowy \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)

[Broszura \(PDF\)](#)

[CAD 3D \(DWG\)](#)

[Certyfikat \(PDF\)](#)

[BIM 3D \(STEP\)](#)