



LX-RETENTIONSEINH.F.ATTIKA SR.79,88,89

LORO-X flange unit for parapet emergency drainage with variable weir and strainer unit, height to be specified

Description

LORO-X VARIOFIT flow aid, strainer basket 210 mm, building-related design please indicate desired weir height when ordering, for emergency drainage with gravity flow, variable weir height, to fit parapet drains series 79, 88 and 89, DN 50 to DN 100



Article information

EAN Code	4038088101162
ETIM Class	EC011398
Outside measurements (HxWxL)	236 x 260 x 260 mm
Weight	3,20 Kg (STK)
Product group	9
Customs tariff number	73072980
Material / Color	Edelstahl, Silber

Usage note

LORO bietet für Hauptentwässerung mit Retention und Notentwässerung mit höhenvariablem Wehr aufeinander abgestimmte VARIOFIT Strömungshilfen, die objektbezogen berechnet und gefertigt werden. Die Höhe des Anstauerelementes der Notentwässerung wird objektbezogen an die Retentionswasserhöhe der Hauptentwässerung mit Retention angepasst. Die aufgeführten Strömungshilfen passen auf die Grundkörper der angegebenen Serien der Attikaentwässerung. Die Montage erfolgt als Strömungshilfe unabhängig von dem Ablaufgrundkörper, sodass die Abdichtung und der Einbau der Strömungshilfe unabhängig voneinander erfolgen können.

Downloads



Alles online

[CAD drawing \(PDF\)](#)
[Aufbauschema \(PDF\)](#)
[BIM 3D \(STEP\)](#)

[Brochure \(PDF\)](#)
[CAD 2D \(DXF\)](#)
[BIM 3D \(IFC\)](#)

[Certificate \(PDF\)](#)
[CAD 3D \(DWG\)](#)