



LX-RETENTIONSEINH.F.ATTIKA SR.79,88,89

LORO-X flange unit for parapet emergency drainage with variable weir and strainer unit, height to be specified

Opis

LORO-X VARIOFIT flow aid, strainer basket 210 mm, building-related design please indicate desired weir height when ordering, for emergency drainage with gravity flow, variable weir height, to fit parapet drains series 79, 88 and 89, DN 50 to DN 100



Dane artykułu

Kod EAN	4038088101162
Klasa ETIM	EC011398
Wymiary zewnętrzne (WxSxD)	236 x 260 x 260 mm
Waga	3,20 Kg (STK)
Grupa produktów	9
Numer taryfy celnej	73072980
Materiał / Kolor	Edelstahl, Silber

Wskazówki dotyczące użytkowania

LORO bietet für Hauptentwässerung mit Retention und Notentwässerung mit höhenvariablem Wehr aufeinander abgestimmte VARIOFIT Strömungshilfen, die objektbezogen berechnet und gefertigt werden. Die Höhe des Anstauerelementes der Notentwässerung wird objektbezogen an die Retentionswasserhöhe der Hauptentwässerung mit Retention angepasst. Die aufgeführten Strömungshilfen passen auf die Grundkörper der angegebenen Serien der Attikaentwässerung. Die Montage erfolgt als Strömungshilfe unabhängig von dem Ablaufgrundkörper, sodass die Abdichtung und der Einbau der Strömungshilfe unabhängig voneinander erfolgen können.

Pobieranie



Alles online

[Rysunek wymiarowy \(PDF\)](#)

[Aufbauschema \(PDF\)](#)

[BIM 3D \(STEP\)](#)

[Broszura \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)

[Certyfikat \(PDF\)](#)

[CAD 3D \(DWG\)](#)